

PS-TSCG3-G PS-TSCG3-H

KEY FEATURES

- Desktop model with replaceable gooseneck microphone and an embedded push-to-talk button (PS-TSCG3-G)
- Wall-mount model with replaceable handheld microphone and an integrated push-to-talk button (PS-TSCG3-H)
- Turnkey paging solution for Q-SYS [TSC-70-G3](#) touchscreens (sold separately or bundled)
- Create custom user control interfaces via Q-SYS control engine
- Supports standard paging elements and non-paging control elements
- Customizable LED status indicators, integrated proximity detection, and ambient light sensors ([TSC-70-G3](#) touchscreen)



Q-SYS PS-TSCG3

Touchscreen Paging Stations

The Q-SYS PS-TSCG3 Touchscreen Paging Station pairs with the TSC-70-G3 touchscreen and Q-SYS control engine to enable paging applications across transportation, education, hospitality, entertainment and beyond. By leveraging Q-SYS Control capabilities, the Q-SYS PS-TSCG3 paging peripheral provides live paging and pre-recorded message playback, alongside traditional functions such as BGM management and device control in a modernized way.

BENEFITS

Modernized User Experience: The Q-SYS Control engine allows you to design fully customized user control interfaces that combine paging functions with device control based on how the space is utilized. It also removes the need for inputting PIN codes for page zone destinations, resulting in a more modern and intuitive user experience.

Complete Q-SYS Paging Solution: The Q-SYS PS-TSCG3 Touchscreen Paging Station lets you take advantage of all existing Q-SYS paging functionality, including priority levels message queueing, preamble playback, pre-recorded message playback and more.

The Right Option for any Space: Available in two models, this page station solution is available as either a desktop model with a replaceable gooseneck microphone and an embedded push-to-talk button (PS-TSCG3-G), as well as a wall-mount model with a replaceable handheld microphone and an integrated push-to-talk button (PS-TSCG3-H).

Q-SYS PS-TSCG3

PS-TSCG3-G

PS-TSCG3-H

Display (Q-SYS TSC-70-G3 Touch Screen)

Type	Projective capacitive (PCAP) multi-touch, high-resolution 24-bit color display	
Viewable screen dimensions (diagonal)	7 in (177.8 mm)	
Resolution	1280 x 800 px	
Aspect Ratio	16:10	
Contrast Ratio	850:1	
Brightness	450 Nits	
Customizable LED status indicators	Yes	
Sensors	Ambient Light Sensor, Proximity Detection	

Audio

Polar pattern	Cardioid	Omnidirectional
Frequency response (-10 dB relative to 1 KHz)	100 Hz to 16 KHz	300 Hz to 11 KHz
Sensitivity	-75 dB ± 3 dB (0 dB = 1 uBar @ 1 KHz)	-70 dB ± 3 dB (0 dB = 1 uBar @ 1 KHz)

General

Dimensions (assembled, with TSC-70-G3)	10.5 x 3.40 x 4.49 in (266 x 86.4 x 114 mm)	10.5 x 4.57 x 2.13 in (266 x 116 x 54.1 mm)
Weight (not including TSC-70-G3)	2.6 lbs (1.18 kg)	3.99 lbs (1.81 kg)
LAN	1x RJ45, 1 Gbps	
PoE (Power over Ethernet)	IEEE 802.3af Type 1 Class 3 (PoE)	
USB	Type C, USB 3.1	
Optional accessories	N/A	PS-DB (desktop base)

Environmental

Ambient operating temperature range	0°-50° C (32°-122° F)	
Humidity	5-85% RH non-condensing	
Storage temperature	-20° to 70° C	