



MP-M Series

MP-M80 | MP-M40

Music and paging mixer/processor

MP-M80

- 8 x mic/line input channels
- 8 x line input channels
- 8 x output zones + 1 music-on-hold output

MP-M40

- 4 x mic/line input channels
- 4 x line input channels
- 4 x output zones + 1 music-on-hold output

All Models

- Supports up to 8 MP-MFC multi-function graphic controllers
- User control from iOS and Android smartphones
- Wireless store-and-forward paging from smartphone
- Mixer with automatic microphone mixer (AMM) function
- 3 year warranty



Introduction

The MP-M Series music and paging mixers offer unprecedented capabilities for processing and routing high-quality foreground/background audio for multi-zone retail and hospitality applications, and provides live mixing functionality for business applications that also require live speech reinforcement, including fitness clubs, hotel meeting rooms, banquet halls etc.

Hardware

The MP-M80 has eight mic/line inputs, eight line inputs and eight zone outputs while the MP-M40 has four mic/line inputs, four line inputs and four zone outputs. Each line input features dual phono jacks (summed to mono) for easy connection to the sources typically found in business music installations.

Both models are equipped with cue bus outputs for auditioning zones and tracks, a USB port for storing and recalling design files, presets and scenes (beyond the mixer's internal memory), both conveniently located on the front panel. They also include two general purpose inputs for external control triggers, and an Ethernet port for connection to a wireless router to allow your system to gain access to the designer and end user control apps (*MP Install* and *MP Manage*.)

Processing

Input processing: All inputs feature comprehensive processing including high and low-pass filters, 4-band parametric EQ, a gate and a dynamics processor that may be configured as an automatic gain control (AGC) or a compressor. The processing is responsive and musical.

Output Processing: Any combination of input channels may be designated as sources for any output zone. Two input channels may be designated as priority sources that will 'duck' the selected input channel for paging/announcements or to allow a higher-priority source to take over. There are also processing blocks for auto-loudness, equalization (1/3 octave GEQ) and limiting. All output channels

include 12 anti-feedback notch filters with a wizard to assist in setting the filters.

Loudspeaker processing: A dedicated loudspeaker processing section contains preset Intrinsic Correction voicings for QSC loudspeakers to maximize the value of the systems. Users may also create, save and recall their own loudspeaker voices using the 6-band fully-parametric equalizer along with high-pass and low-pass filters with a choice of filters (Linkwitz-Riley or Butterworth) and slope (12, 18 or 24 dB/octave).

Mixer: An integral stereo mixer may be used for reinforcement of live performance or for conference/presentation mixing. Effects processing and a gain sharing automatic microphone mixer are both available. Any inputs can be assigned to the mixer and its output may be assigned to any combination of output zones.

Software

MP Install app (for iOS/Android tablets, Windows and Mac OS PCs) is used by designers and installers to configure and tune the system. Designers can use the app online or offline to pre-configure a system without connecting to hardware. All MP-M Series parameters and settings are accessible from the app including an intuitive Workflow Wizard to assist installers with navigating the room tuning process and expediting commissioning tasks. *MP Install* also allows for customized control configuration for the MP-M Series' end user control peripherals.

MP Manage app (for iOS/Android tablets and smartphones) provides wireless day-to-day operation of basic system functions including zone level control and source selection, scene recall, scheduling, and mixer control. It also offers a unique store-and-forward paging functionality to the MP-M Series mixer. The installer may restrict or allow which functions are available to the staff. Multiple user profiles can be created allowing the installer or a facility staff member to grant individuals access to only those functions they need.

MP-M Series

Model	MP-M40	MP-M80
Inputs		
Total	8	16
Mic/Line	4 (Euroblock)	8 (Euroblock)
RCA	4 (mono-summed RCA pairs)	8 (mono-summed RCA pairs)
Outputs		
Total	6	10
Line	4 (Euroblock, balanced)	8 (Euroblock, balanced)
Music-on-Hold	1 (Euroblock, transformer balanced)	1 (Euroblock, transformer balanced)
Cue (phones)	1 (3.5 mm, stereo)	1 (3.5 mm, stereo)
Audio		
Sampling frequency	48 kHz	
Processing	32-bit floating point	
THD	<0.005%, +4 dBu and -2 dB; 20 Hz-20 kHz, unity gain, any input to any output	
Frequency response	20 Hz-20 kHz +/-0.5 dB, mic/line or line input to any line output	
Dynamic range	>106 dB unweighted	
Crosstalk	>90 dB typical, >80 dB max	
Gain (mic inputs)	51 dB	
Maximum input level	+24 dBu (mic/line inputs), +10 dBV (line inputs)	
Maximum output level	+21 dBu (line-level outputs), +10 dBV (music on hold)	
Phantom power	All microphone inputs (+12 volts)	
Latency	2.3 msec	
Input Processing		
EQ	4-band parametric EQ with high/low shelving option, variable 24 dB/octave HPF and LPF	
Dynamics	Gate, choice of Auto Gain Control (AGC) or compressor	
Output Processing		
EQ	1/3 octave GEQ	
Anti-feedback filters	12-band variable notch filters	
Dynamics	Comp/limiter, ducker, loudness	
Delay	100 msec	
Loudspeaker tunings	Factory: Intrinsic Correction™ voicing for QSC loudspeakers User: 6-band parametric EQ, HPF & LPF (Linkwitz-Riley or Butterworth; 12, 18 or 24 dB/octave)	
Control Accessories		
MP-MFC	Optional wall controller	
MP Install	For configuration/design functions (for iOS/Android tablets, Windows and Mac OS PCs),	
MP Manage	For end user control functions (for iOS/Android tablets and smartphones)	
Other Connections		
Ethernet	1 x RJ45 for connection to Wi-Fi router (user supplied)	
MP-MFC ports	2 x RJ45	
USB	2 USB-A (firmware & configuration uploads, USB Wi-Fi)	
GPI	2 inputs (Euroblock)	

Power requirements	100-240VAC, 50-60 Hz, universal supply, IEC inlet
Indicators	Blue POWER LED, blue STATUS LED
Dimensions (Net)	1.75 in x 19 in x 14 in (4.5 cm X 48.3 cm X 35.6 cm)
Weight	
Shipping	11.0 lb (5.0 kg)
Net	7.0 lb (3.2 kg)

As part of QSC's ongoing commitment to product development, specifications are subject to change without notice.



1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174
 © 2018 QSC, LLC all rights reserved. QSC and the QSC logo are registered trademarks of QSC, LLC in the U.S. Patent and Trademark office and other countries. All other trademarks are the property of their respective owners. Patents may apply or be pending.

MP-M Spec Sheet 07/16/2018

